

Kelln Centric Submersible 24V-DC

High Efficient Submersible Pump

- ◆ 22-30V Battery Operation
- ◆ Up to 60 Ft Lifts
- ◆ Flow Rate up to 12.1 Imp. Gals
maintenance free brushless motor
technology, water filled ! No
submergence limits liked other brushed
motors have
- ◆ Controller with float & probe
terminals
- ◆ Over charge & over discharge protection
- ◆ LED Indication of well probe, float
switch, Pump operation and system
power
- ◆ Fits in 4" well casing

Applications:

- Livestock watering
- Pond management
- Remote homes
- Irrigation
- Village water supply



24V Performance of Kelln - CENTRIC Centrifugal Pump 4" Submersible Pump With ETADRIVE and ME24 Controller					
Lift	Power	Current	Flow rate		
Feet	Watts	Amps	LPM	US GPM	IMP GPM
16	200	8.6	55	14.5	12.1
26	200	8.6	49	12.9	10.8
33	200	8.6	45	11.9	9.9
43	200	8.5	39	10.3	8.6
50	190	8.3	34	9.0	7.5
60	180	7.9	25	6.6	5.5
66	180	7.5	17	4.5	3.7

Authorized Distributor:



50 James Street, Box 94 Lumsden Saskatchewan Canada Tel (306) 731-2224 Fax (306) 731-2774

Pumping Specs for ETAPUMP Centric 24V-DC

		Amps	Gals	232	242	264	442	464	664	232	242	264	442	464	664
Lift	GPM	Per Hr.	Per Day	Panels	Panels	Panels	Panels	Panels	Panels	C/C Prs	C/C Prs	C/C Prs	C/C Prs	C/C Prs	C/C Prs
16	12.10	8.60	726	1014	1267	1976	2533	3951	5927	68	85	132	169	264	396
26	10.80	8.60	648	905	1131	1764	2261	3527	5290	61	76	118	151	236	353
33	9.90	8.60	594	829	1037	1617	2073	3233	4849	56	70	108	139	216	324
43	8.60	8.50	516	729	911	1421	1822	2842	4262	49	61	95	122	190	285
50	7.50	8.30	450	651	814	1269	1627	2538	3807	44	55	85	109	170	254
60	5.50	7.90	330	502	627	978	1254	1955	2933	34	42	66	84	131	196
66	3.70	7.50	222	356	444	693	888	1386	2078	24	30	47	60	93	139

All gallons are in Imperial Measurements

Warranty

The Kelln Centric Pump and controllers are warranted to be free from defects in material and workmanship for one year from date of purchase.

Common Pumping Situations

Situation

75 Cow/Calf Pairs (battery operated)
26 Feet Lift / 4" casing / 10 GPM Recovery

Pump Model Kelln Centric232

1 - Kelln Centric 24V – DC Pump
1 - Pump Controller
2 - 32 Watt Shatterproof Solar panels
1 - Double Panel Stand
1 - Low Voltage Disconnect
1 - Float Switch (30' relay operated)
70 - Lin Ft. Electrical Cable
1 - Wiring Package (Prewired Plug-in ready)
1 - Battery Box

Required But Not Included

1 – Pole (2 3/8" O.D.) for panel Stand
2 – Trojan SCS 225 Trojan Batteries

System Price \$ 2195.00

**For Cable, Poly Hose and Safety Rope add
\$3.00 Lin.Ft. X Depth of Pump + 10 Feet**

Situation

170 Cow/Calf Pairs (battery operated)
50 Feet Lift / 4" casing / 10 GPM Recovery

Pump Model Kelln Centric464

1 - Kelln Centric 24V – DC Pump
1 - Pump Controller
4 - 64 Watt Shatterproof Solar panels
2 - Double Panel Stand
1 - Low Voltage Disconnect
1 - Float Switch (30' relay operated)
70 - Lin Ft. Electrical Cable
1 - Wiring Package (Prewired Plug-in ready)
1 - Heavy Duty Battery Box

Required But Not Included

1 – Pole (2 3/8" O.D.) for panel Stand
4– Trojan T105 6 Volt Batteries

System Price \$ 3795.00

**For Cable, Poly Hose and Safety Rope add
\$3.00 Lin.Ft. X Depth of Pump + 10 Feet**